

Certification

Issued Under the Authority of the
Federal Communications Commission

By:

PHOENIX TESTLAB GmbH
Koenigswinkel 10
32825 Blomberg,
Germany

Date of Grant: 06/26/2014

Application Dated: 06/25/2014

Fibocom Wireless Inc.
5/F, Tower A, Technology Building II,
1057# Nanhai Blvd,
Shenzhen, 518067
China

Attention: Tao Zhu , Marketing Director

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE,
and is VALID ONLY for the equipment identified hereon for use under the
Commission's Rules and Regulations listed below.

FCC IDENTIFIER: ZMOH38F
Name of Grantee: Fibocom Wireless Inc.
Equipment Class: PCS Licensed Transmitter
Notes: WCDMA Module

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	824.2 - 848.8	1.832	0.03 PM	245KGXW
	22H	824.2 - 848.8	0.532	0.03 PM	244KG7W
	24E	1850.2 - 1909.8	0.966	0.01 PM	245KGXW
	24E	1850.2 - 1909.8	0.435	0.01 PM	247KG7W
	22H	826.4 - 846.6	0.193	0.03 PM	4M07F9W
	24E	1852.4 - 1907.6	0.183	0.01 PM	4M06F9W

Licensed Modular Transmitter. Output Power listed is conducted. This device contains functions that are not operational in U.S Territories. This filing is only applicable for US operations. This OEM module is approved for use in products operating as fixed or mobile transmitting device. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. A separate approval is required for portable operating configurations, as defined in 2.1093 of the rules. The final product operating with this transmitter must include operating instructions and applicable warnings for end users and installers to satisfy RF exposure compliance requirements. Antenna gain must meet RF exposure and max radiated output power limits of the applicable rule section. The max. antenna gain for this device as reported to the FCC is: 2.5dBi (850MHz) and 2.5dBi (1900MHz). This Grant is valid only when the device is sold to OEM integrators and the OEM integrators are instructed to ensure that the end user has no manual instructions to remove or install the device.